

P-80® Grip-It
Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: 2023-07-12

Replaces version 2022-11-18

SECTION 1: Identification

1.1 Product identifier

Trade name **P-80® Grip-It**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses
Temporary Rubber Assembly Lubricant
Industrial use
Do not use for private purposes (household)

1.3 Details of the supplier of the safety data sheet

International Products Corporation
201 Connecticut Drive
Burlington NJ 08016
United States

Telephone: +1 (609) 386-8770
Telefax: +1 (609) 386-8438
e-mail: mkt@ipcol.com
Website: <https://www.ipcol.com/>

1.3.1 Additional information

| Manufacturer | | | | | | |
|------------------------------------|-----------------------|------------------|---------------|----------------|--|--|
| Name | Street | Postal code/city | Country | Telephone | e-Mail | Website |
| International Products Corporation | 201 Connecticut Drive | 08016 Burlington | United States | 1-609-386-8770 | mkt@ipcol.com | www.ipcol.com |

1.4 Emergency telephone number

1.4.1 Emergency information service **+1 (609) 386-8770**
This number is only available during the following office hours: Mon-Fri 08:00 AM - 04:30 PM, Eastern Time

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

| Classification acc. to GHS | | | | |
|----------------------------|--------------------|----------|---------------------------|------------------|
| Section | Hazard class | Category | Hazard class and category | Hazard statement |
| A.4S | skin sensitization | 1 | Skin Sens. 1 | H317 |

For full text of abbreviations: see SECTION 16.

2.2 Label elements

P-80® Grip-It
Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: 2023-07-12

Replaces version 2022-11-18


Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word warning

- Pictograms

GHS07



| Hazard statements. | | | |
|--------------------|---|------|-------------------------------------|
| Signal word | Symbol(s) | Code | Hazard statement. |
| warning |  | H317 | may cause an allergic skin reaction |

| - Precautionary statements | |
|----------------------------|--|
| Code | Precautionary statements. |
| P261 | avoid breathing dust/fume/gas/mist/vapors/spray. |
| P272 | contaminated work clothing must not be allowed out of the workplace. |
| P280 | wear protective gloves/protective clothing/eye protection/face protection. |
| P302+P352 | if on skin: Wash with plenty of water. |
| P321 | specific treatment (see on this label). |
| P333+P313 | if skin irritation or rash occurs: Get medical advice/attention. |
| P363 | wash contaminated clothing before reuse. |
| P501 | dispose of contents/container to industrial combustion plant. |

2.2.1.7- Hazardous ingredients for labelling

Polyetheleneimine

2.3 Other hazards

Hazards not otherwise classified

| Supplemental hazard information | |
|---------------------------------|--|
| Code | Supplemental hazard information |
| HNOC001 | may be harmful if swallowed (GHS category 5: acutely toxic - oral). |
| HNOC010 | harmful to aquatic life with long lasting effects (GHS category 3: aquatic toxicity - acute and/or chronic). |

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.

P-80® Grip-It

Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: 2023-07-12

Replaces version 2022-11-18


SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

| Name of substance | Identifier | Wt% | Classification acc. to GHS | Pictograms |
|-------------------|---------------------|-----------|---|---|
| Water | CAS No 7732-18-5 | ≥ 90 | | |
| Polyetheleneimine | CAS No 9002-98-6 | 0.5 – < 1 | Acute Tox. 4 / H302 Eye Irrit. 2A / H319 Skin Sens. 1A / H317 |  |

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

P-80® Grip-It

Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: 2023-07-12

Replaces version 2022-11-18

5.2 Special hazards arising from the substance or mixture

5.3 Advice for firefighters

Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: Sawdust, Kieselgur (diatomite), Sand, Universal binder

Appropriate containment techniques

Use of adsorbent materials.

6.4 Reference to other sections

Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

- Specific designs for storage rooms or vessels

- Storage temperature

Recommended storage temperature: 2 – 30 °C

P-80® Grip-It

Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: 2023-07-12

Replaces version 2022-11-18

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)
this information is not available

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection. Use protective eyewear to guard against splash of liquids. Work with safety glasses.

Skin protection

- Hand protection

Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Type of material

PVC: polyvinyl chloride, PE: polyethylene, NR: natural rubber, latex, CR: chloroprene (chlorobutadiene) rubber, NBR: acrylonitrile-butadiene rubber, IIR: isobutene-isoprene (butyl) rubber, FKM: fluoro-elastomer, PVA: polyvinyl alcohol, Nitrile

- Material thickness

At least 4 mil.

- Breakthrough times of the glove material

>240 minutes (permeation: level 5)

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

[In case of inadequate ventilation] wear respiratory protection. Half mask (EN 140). Type : A (against organic gases and vapors with a boiling point of > 65 °C , color code: Brown).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

P-80® Grip-It

Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: 2023-07-12

Replaces version 2022-11-18

| | |
|----------------|-----------------------|
| Physical state | liquid |
| Color | colorless-clear |
| Particle | not relevant (liquid) |
| Odor | odorless |

Other safety parameters

| | |
|---|-----------------------------------|
| pH (value) | 9.8 – 11.3 (25 °C) |
| Melting point/freezing point | 0 °C |
| Initial boiling point and boiling range | 100 °C |
| Flash point | not determined |
| Evaporation rate | Not determined |
| Flammability (solid, gas) | not relevant, (fluid) |
| Vapor pressure | not determined |
| Density | 0.995 – 0.999 g/ml at 25 °C |
| Vapor density | this information is not available |

Solubility(ies)

| | |
|--------------------|----------------------------|
| - Water solubility | miscible in any proportion |
|--------------------|----------------------------|

Partition coefficient

| | |
|-----------------------------|-----------------------------------|
| - n-octanol/water (log KOW) | this information is not available |
|-----------------------------|-----------------------------------|

| | |
|---------------------------|----------------|
| Auto-ignition temperature | not determined |
|---------------------------|----------------|

Viscosity

| | |
|-----------------------|---|
| - Kinematic viscosity | 1.002 – 20.04 mm ² /s at 25 °C |
| - Dynamic viscosity | 1 – 20 cP at 25 °C |

P-80® Grip-It

Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: 2023-07-12

Replaces version 2022-11-18

| | |
|----------------------|------|
| Explosive properties | none |
| Oxidizing properties | none |

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability Shelf-life

Shelf-life. Two years from the date of manufacture.

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not mix with other chemicals.

10.5 Incompatible materials

Avoid extended contact with uncured paint, zinc, aluminum, cold rolled steel, or copper and its alloys. Avoid contact with polycarbonate, polymethyl methacrylate, and polyphenylene oxide as these plastics may craze over time. Refer to product's compatibility sheets for further details.

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Basis of test data.

Classification procedure

The classification is based on tested mixture.

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if swallowed.

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

P-80® Grip-It

Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: 2023-07-12

Replaces version 2022-11-18

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability**Biodegradation**

Not readily biodegradable.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods**Sewage disposal-relevant information**

May be disposed according to local, state and federal regulations.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

P-80® Grip-It
Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: 2023-07-12

Replaces version 2022-11-18

SECTION 14: Transport information

- 14.1 UN number** not subject to transport regulations
- 14.2 UN proper shipping name** not assigned
- 14.3 Transport hazard class(es)** none
- 14.4 Packing group** not assigned
- 14.5 Environmental hazards** non-environmentally hazardous acc. to the dangerous goods regulations
- 14.6 Special precautions for user**
There is no additional information.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed (ACTIVE)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

None of the ingredients are listed.

- Specific Toxic Chemical Listings (EPCRA Section 313)

None of the ingredients are listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

None of the ingredients are listed.

Clean Air Act

None of the ingredients are listed.

Right to Know Hazardous Substance List

- Hazardous Substance List (NJ-RTK)

none of the ingredients are listed

National inventories

| Country | National inventories | Status |
|---------|----------------------|-------------------------------------|
| US | TSCA | all ingredients are listed (ACTIVE) |

Legend

TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

P-80® Grip-It
Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: 2023-07-12

Replaces version 2022-11-18

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

| Abbr. | Descriptions of used abbreviations |
|---------------|---|
| 49 CFR US DOT | 49 CFR U.S. Department of Transportation |
| Acute Tox. | Acute toxicity |
| CAS | Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances) |
| CMR | Carcinogenic, Mutagenic or toxic for Reproduction |
| DGR | Dangerous Goods Regulations (see IATA/DGR) |
| Eye Dam. | Seriously damaging to the eye |
| Eye Irrit. | Irritant to the eye |
| GHS | "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations |
| IATA | International Air Transport Association |
| IATA/DGR | Dangerous Goods Regulations (DGR) for the air transport (IATA) |
| IMDG | International Maritime Dangerous Goods Code |
| OSHA | Occupational Safety and Health Administration (United States) |
| PBT | Persistent, Bioaccumulative and Toxic |
| RTECS | Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information) |
| Skin Sens. | Skin sensitization |
| vPvB | Very Persistent and very Bioaccumulative |

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

The classification is based on tested mixture.

Classification on the basis of specific effects on human health (CMR effects)

The classification is based on:

Harmonized (legal) classification.

Classification on the basis of environmental effects

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

P-80® Grip-It
Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: 2023-07-12

Replaces version 2022-11-18

List of relevant phrases (code and full text as stated in section 2 and 3)

| Code | Text |
|------|--------------------------------------|
| H302 | Harmful if swallowed. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.