

P-80® THIX
Temporary Rubber Lubricant Gel

Date of issue: 2023-07-12

Replaces version 2022-11-18

SECTION 1: Identification

1.1 Product identifier

Trade name **P-80® THIX**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses
Temporary Rubber Assembly Lubricant
Industrial use
Do not use for private purposes (household)

1.3 Details of the supplier of the safety data sheet

International Products Corporation
201 Connecticut Drive
Burlington NJ 08016
United States

Telephone: +1 (609) 386-8770
Telefax: +1 (609) 386-8438
e-mail: mkt@ipcol.com
Website: <https://www.ipcol.com/>

1.3.1 Additional information

Manufacturer						
Name	Street	Postal code/city	Country	Telephone	e-Mail	Website
International Products Corporation	201 Connecticut Drive	08016 Burlington	United States	1-609-386-8770	mkt@ipcol.com	www.ipcol.com

1.4 Emergency telephone number

1.4.1 Emergency information service **+1 (609) 386-8770**
This number is only available during the following office hours: Mon-Fri 08:00 AM - 04:30 PM, Eastern Time

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Classification acc. to GHS				
Section	Hazard class	Category	Hazard class and category	Hazard statement
A.4S	skin sensitization	1	Skin Sens. 1	H317

For full text of abbreviations: see SECTION 16.

2.2 Label elements

P-80® THIX
Temporary Rubber Lubricant Gel

Date of issue: 2023-07-12

Replaces version 2022-11-18

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word warning

- Pictograms

GHS07



Hazard statements.			
Signal word	Symbol(s)	Code	Hazard statement.
warning		H317	may cause an allergic skin reaction

- Precautionary statements	
Code	Precautionary statements.
P261	avoid breathing dust/fume/gas/mist/vapors/spray.
P272	contaminated work clothing must not be allowed out of the workplace.
P280	wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	if on skin: Wash with plenty of water.
P321	specific treatment (see on this label).
P333+P313	if skin irritation or rash occurs: Get medical advice/attention.
P363	wash contaminated clothing before reuse.
P501	dispose of contents/container to industrial combustion plant.

2.2.1.7- Hazardous ingredients for labelling

2-methylisothiazol-3(2H)-one, 2-octyl-3(2H)-isothiazolone

2.3 Other hazards

Special danger of slipping by leaking/spilling product.

Hazards not otherwise classified

Supplemental hazard information	
Code	Supplemental hazard information
HNOC001	may be harmful if swallowed (GHS category 5: acutely toxic - oral).
HNOC010	harmful to aquatic life with long lasting effects (GHS category 3: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.

P-80® THIX
Temporary Rubber Lubricant Gel

Date of issue: 2023-07-12

Replaces version 2022-11-18



SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
2-methylisothiazol-3(2H)-one	CAS No 2682-20-4	< 0.05	Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 2 / H330 Skin Corr. 1B / H314 Eye Dam. 1 / H318 Skin Sens. 1A / H317	
2-octyl-3(2H)-isothiazolone	CAS No 26530-20-1	< 0.05	Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 2 / H330 Skin Corr. 1 / H314 Eye Dam. 1 / H318 Skin Sens. 1A / H317	

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

P-80® THIX

Temporary Rubber Lubricant Gel

Date of issue: 2023-07-12

Replaces version 2022-11-18

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: Sawdust, Kieselgur (diatomite), Sand, Universal binder

Appropriate containment techniques

Use of adsorbent materials.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

P-80® THIX
Temporary Rubber Lubricant Gel

Date of issue: 2023-07-12

Replaces version 2022-11-18

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

- Specific designs for storage rooms or vessels
- Storage temperature

Recommended storage temperature: 2 – 30 °C

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	triethanolamine	102-71-6	PEL (CA)		5						Cal/ OSHA PEL
US	triethanolamine	102-71-6	TLV®		5						ACGIH® 2023

Notation

Ceiling-C
STEL

ceiling value is a limit value above which exposure should not occur
short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
2-methylisothiazol-3(2H)-one	2682-20-4	DNEL	0.021 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
2-methylisothiazol-3(2H)-one	2682-20-4	DNEL	0.043 mg/m ³	human, inhalatory	worker (industry)	acute - local effects

Relevant PNECs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
2-methylisothiazol-3(2H)-one	2682-20-4	PNEC	3.39 µg/l	aquatic organisms	freshwater	short-term (single instance)
2-methylisothiazol-3(2H)-one	2682-20-4	PNEC	3.39 µg/l	aquatic organisms	marine water	short-term (single instance)
2-methylisothiazol-3(2H)-one	2682-20-4	PNEC	0.23 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)

P-80® THIX
Temporary Rubber Lubricant Gel

Date of issue: 2023-07-12

Replaces version 2022-11-18

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
2-methylisothiazol-3(2H)-one	2682-20-4	PNEC	0.047 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-octyl-3(2H)-isothiazolone	26530-20-1	PNEC	2.2 µg/l	aquatic organisms	freshwater	short-term (single instance)
2-octyl-3(2H)-isothiazolone	26530-20-1	PNEC	0.22 µg/l	aquatic organisms	marine water	short-term (single instance)
2-octyl-3(2H)-isothiazolone	26530-20-1	PNEC	47.5 µg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2-octyl-3(2H)-isothiazolone	26530-20-1	PNEC	4.75 µg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-octyl-3(2H)-isothiazolone	26530-20-1	PNEC	8.2 µg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection. Use protective eyewear to guard against splash of liquids. Work with safety glasses.

Skin protection

- Hand protection

Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Type of material

PVC: polyvinyl chloride, PE: polyethylene, NR: natural rubber, latex, CR: chloroprene (chlorobutadiene) rubber, NBR: acrylonitrile-butadiene rubber, IIR: isobutene-isoprene (butyl) rubber, FKM: fluoro-elastomer, PVA: polyvinyl alcohol, Nitrile

- Material thickness

At least 4 mil.

- Breakthrough times of the glove material

>240 minutes (permeation: level 5)

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

[In case of inadequate ventilation] wear respiratory protection. Half mask (EN 140). Type : A (against organic gases and vapors with a boiling point of > 65 °C , color code: Brown).

P-80® THIX
Temporary Rubber Lubricant Gel

Date of issue: 2023-07-12

Replaces version 2022-11-18

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid (gel)
Color	white-cream
Particle	not relevant (liquid)
Odor	characteristic

Other safety parameters

pH (value)	7.5 – 9 (25 °C)
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	not determined
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	not determined
Density	0.96 – 0.98 g/ml at 25 °C
Vapor density	this information is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	not determined

Viscosity

P-80® THIX
Temporary Rubber Lubricant Gel

Date of issue: 2023-07-12

Replaces version 2022-11-18

- Kinematic viscosity	>12,024 mm ² /s at 25 °C
- Dynamic viscosity	>12,000 cP at 25 °C
Explosive properties	none
Oxidizing properties	none

SECTION 10: Stability and reactivity**10.1 Reactivity**

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability Shelf-life

Shelf-life. Two years from the date of manufacture.

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not mix with other chemicals.

10.5 Incompatible materials

Avoid extended contact with uncured paint, zinc, aluminum, cold rolled steel, or copper and its alloys. Avoid contact with polycarbonate, polymethyl methacrylate, and polyphenylene oxide as these plastics may craze over time. Refer to product's compatibility sheets for further details.

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

Basis of test data.

Classification procedure

The classification is based on tested mixture.

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)**Acute toxicity**

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if swallowed.

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

P-80® THIX
Temporary Rubber Lubricant Gel

Date of issue: 2023-07-12

Replaces version 2022-11-18

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
2-methylisothiazol-3(2H)-one	2682-20-4	LC50	4.77 mg/l	fish	96 h
2-methylisothiazol-3(2H)-one	2682-20-4	EC50	1.7 mg/l	aquatic invertebrates	24 h
2-methylisothiazol-3(2H)-one	2682-20-4	ErC50	>0.072 mg/l	algae	96 h
2-octyl-3(2H)-isothiazolone	26530-20-1	LC50	0.122 mg/l	fish	96 h
2-octyl-3(2H)-isothiazolone	26530-20-1	ErC50	0.15 mg/l	algae	96 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
2-methylisothiazol-3(2H)-one	2682-20-4	EC50	1.4 mg/l	aquatic invertebrates	21 d
2-methylisothiazol-3(2H)-one	2682-20-4	ErC50	0.22 mg/l	algae	120 h

P-80® THIX
Temporary Rubber Lubricant Gel

Date of issue: 2023-07-12

Replaces version 2022-11-18

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Sewage disposal-relevant information

May be disposed according to local, state and federal regulations.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number	not subject to transport regulations
14.2 UN proper shipping name	not assigned
14.3 Transport hazard class(es)	none
14.4 Packing group	not assigned
14.5 Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6 Special precautions for user	
There is no additional information.	

P-80® THIX
Temporary Rubber Lubricant Gel

Date of issue: 2023-07-12

Replaces version 2022-11-18

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

None of the ingredients are listed.

Clean Air Act

None of the ingredients are listed.

National inventories

Country	National inventories	Status
EU	REACH Reg.	all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)

Legend

REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH® 2023	From ACGIH®, 2023 TLVs® and BEIs® Book. Copyright 2023. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control

P-80® THIX
Temporary Rubber Lubricant Gel

Date of issue: 2023-07-12

Replaces version 2022-11-18

Abbr.	Descriptions of used abbreviations
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

The classification is based on tested mixture.

Classification on the basis of specific effects on human health (CMR effects)

The classification is based on:

Harmonized (legal) classification.

Classification on the basis of environmental effects

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

P-80® THIX
Temporary Rubber Lubricant Gel

Date of issue: 2023-07-12

Replaces version 2022-11-18

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.