

609-386-8770 | Fax: 609-386-8438 | www.ipcol.com

Storage & Handling Procedures for Aqueous Cleaners

| Micro-90 [®] | Micro Green Clean® | LF2100 [®] | Micro [®] A07 |
|-----------------------|-----------------------------|------------------------|------------------------|
| Surface-Cleanse/930® | Zymit [®] Low-Foam | Zymit Pro [®] | |

- Store between 5°C 30°C (40°F 90°F) in a cool, dry, well-ventilated area. Protect containers from sunlight and keep them closed when not in use. Use only stainless steel, polyethylene, or plastic-lined containers for storage. Do not store Micro-90, Micro Green Clean, or LF2100 in contact with aluminum, zinc, copper, or their alloys.
- 2. Dilute before use. Typically, a 1.0% 2.0% solution will be effective.
- 3. For proper inventory control, it is best to use the oldest product first. Each container has a lot number that gives the date (YYMMDD) that the material was produced. This will prevent using new material when older stock is available.
- 4. Compatible with most metals, plastics, and other hard surfaces; however, users are encouraged to ensure their parts are compatible with these cleaners before they are put into production. Compatibility studies for common metals and plastics are available.
- 5. Cleaning action may be improved by increasing temperature, dwell time, concentration, and by using ultrasonics or agitation.

6. DO NOT MIX CLEANERS WITH OTHER PRODUCTS.

7. For safety details, please refer to the appropriate Safety Data Sheet (SDS), which can be downloaded from our website: <u>www.ipcol.com</u>, or requested by calling 609-386-8770.

| Product | Specific Gravity (g/ml @ 25 ° C) | pH (concentrate) | Maximum suggested operating temperature | Shelf Life |
|----------------------|-------------------------------------|---------------------|---|------------|
| Micro-90 | 1.130 - 1.145 | 9.0 - 9.9 | 65 °C (149 °F) | 5 years |
| Micro Green Clean | 1.050 - 1.110 | 9.0 - 10.0 | 65 °C (149 °F) | 5 years |
| LF2100 | 1.160 - 1.180 | 9.0 - 9.9 | 65 °C (149 °F) | 5 years |
| Micro A07 | 1.120 - 1.160 | 2.0 - 3.0 | 65 °C (149 °F) | 5 years |
| Surface- Cleanse/930 | 0.990 - 1.010 | 5.5 - 7.5 | 50 °C (122°F) | 5 years |
| Zymit Low-Foam | 1.025 - 1.065 | 6.9 - 8.4 | 55 °C (131 °F) | 2 years |
| Zymit Pro | 1.040 - 1.120 | 6.9 - 8.4 | 55 °C (131 °F) | 2 years |

Specifications

For Sales and Service in Europe

Cimcool Industrial Products BV /Cimcool Europe BV Schiedamsedijk 20, 3134 KK Vlaardingen, The Netherlands Tel. +31(0)10 445 0050

cimcool.eu@duboischemicals.com